

45-Tooth Reversible Ratchet Head Setting Series



Features:

- *Double window scale,plastic grip,high precision, resulting in fast and efficient operation.
- *The 45-tooth reversible ratchet head for both clockwise and counterclockwise operation.
- *+/-3% accuracy in clockwise direction exceeds international specifications.(+/-4% accuracy when the torque $\geq 500\text{N.m}$)
- *Ergonomic soft TPR grips are comfortable to use.
- *Unique, stay-in-place,Lock Ring makes adjustments easier and secures selected torque from accidental change.
- *Metric scale with fine increments and reference English scales are easy to read and set.
- *The identity code marked on each wrench makes it possible to keep accurate records.
- *Each wrench comes with the Calibration Certificate.

Technical Specification -Metric Scale

Part Code	Drive	Torque Range		Graduation Scale	Length	Width	Weight	Packing size	Weight
		N.m	Lb.ft	N.m	mm	mm	kg	cm	Kg
SL1012	1/4"	2.5-12	20-105*	0.025	285	38	0.54	49*8*7	0.48
SL1020	1/4"	4.0-20	30-180*	0.05	285	38	0.54	49*8*7	0.48
SL2030	3/8"	6.0-30	50-250*	0.075	313	38	0.68	49*8*7	0.48
SL3030	1/2"	6.0-30	50-250*	0.075	313	38	0.68	49*8*7	0.48
SL2060	3/8"	10-60	9-45	0.125	383	38	0.82	49*8*7	0.48
SL3060	1/2"	10-60	9-45	0.125	383	38	0.82	49*8*7	0.48
SL2100	3/8"	20-100	15-75	0.25	438	38	0.9	49*8*7	0.48
SL3100	1/2"	20-100	15-75	0.25	438	38	0.9	49*8*7	0.48
SL2125	3/8"	25-125	20-90	0.25	438	38	0.9	49*8*7	0.48
SL3125	1/2"	25-125	20-90	0.25	438	38	0.9	49*8*7	0.48
SL3200	1/2"	40-200	30-150	0.5	463	40	1.02	49*8*7	0.48
SL3335	1/2"	65-335	50-250	0.75	523	40	1.16	69*9*6	0.58
SL4335	3/4"	65-335	50-250	0.75	523	40	1.2	69*9*6	0.58
SL3335L	1/2"	65-335	50-250	0.75	700	40	1.95	90*11*8	1.16
SL4335L	3/4"	65-335	50-250	0.75	700	40	2	90*11*8	1.16
SL4400	3/4"	80-400	60-300	1	700	57	2.75	90*11*8	1.16
SL4500S	3/4"	100-500	80-400	1.25	700	57	2.75	90*11*8	1.16
SL4500	3/4"	100-500	80-400	1.25	840	60	4.04	90*11*8	1.16

SL4800	3/4"	160-800	120-600	2	1040	60	4.93	129*14*10	1.86
SL5800	1"	160-800	120-600	2	1040	60	4.93	129*14*10	1.86
SL41000	3/4"	200-1000	150-750	2.5	1040	60	4.93	129*14*10	1.86
SL51000	1"	200-1000	150-750	2.5	1040	60	4.93	129*14*10	1.86
SL51500	1"	300-1500	200-1100	3	1250	72	8.2	129*14*10	1.86
SL52000	1"	400-2000	300-1500	5	1250	72	8.2	129*14*10	1.86
SL53000	1"	600-3000	400-2200	7.5	1250	72	9.5	129*14*10	1.86

Unit is Lb.in